

Technical data sheet

Article number:
156-00816

T30LRFT6



| | |
|--------------------------------------|---|
| Product Group | 2-piece fixing ties with fir tree, with disc, for round holes |
| Product Family | Fir tree parts FT6 |
| Material | Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) |
| Colour | Black (BK) |
| Application Tool | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP |
| Bundle Ø max. | 65.0 mm |
| Bundle Ø min. | 5.0 mm |
| Cable Tie | Polyamide 6.6, heat stabilised (PA66HS) |
| Fixation Method | Fir Tree |
| Flammability | UL 94 HB |
| Foot Part | Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) |
| for Hole Ø (FH) | 6.4 - 7.1 mm |
| Height (H) | 1.3 mm |
| Length (L) | 260 mm |
| Length (L2) | 11.6 mm |
| Min.Tensile Strength | 180 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | bag |
| Pack Cont. | 500 pcs. |
| Panel Thickness | 3.00 mm |
| Panel Thickness min. (metric) | 0.75 mm |
| ROHS compliant | Yes |
| Variant | Inside Serrated |
| Width (W) | 3.3 mm |

